



National Fire Equipment Ltd.

MODEL 6175M-001

HYDRANT HOSE HOUSE

FABRICATION DETAILS

Steel construction:

16 ga. satin coat sheet steel. 600 lbs. Empty

Framing:

Top - Solid Roof Protection Bottom - Open Type

Door Stopper & Roof Support:

2" (5.08 cm) wide x 1" (2.54 cm) x 3 3/16" (.48 cm) channel

Door reinforcing (all around):

2" (5.08 cm) wide x 1/2" (1.27 cm) deep x 16 ga. channel

Door Lock (R.H. door only) Chrome plated handle

Suitable brackets for accessories (optional-please specify)

Piano Hinge-both doors**Shelves:**

22 1/2" (57.15 cm) wide x 2" (5.08 cm) x 57 3/4" (146.68 cm) long*
1/2" (12.7 cm) dia. hole (6 at back, 3 on each side, 1 in front.)

*(optional-please specify)

Finish one coat grey primer and two coats baked red enamel

Supplied, knocked down with assembly instructions.

Supplied by others:

Water Hydrant
Cement base
Anchor bolt

IMPORTANT: Specify quantity of shelves and location prior to ordering.

Note:

Not designed for sea water environment.
Contact us for sea water protection options.



We reserve the right to alter cabinet specifications and dimensions.
Please contact our local representative for updated approval drawings
prior to base construction and ordering.

Pad Lock Hasp Detail on Page 2

